
Study and Simulation of Robotic Finger Movements



SPECIAL PROJECT

K.Puhazhendi

की, ब. केन्द्र पुरवकाख्य I. D. C. LIBRARY.

Study and Simulation of Robotic Finger Movements

K.Puhazhendi

Submitted in partial fulfilment of the requirements for the Post-graduate degree in Industrial Design

Guide Prof A.G.Rao

INDUSTRIAL DESIGN CENTRE, I.I.T.,POWAI,BOMBAY-400 076 APRIL, 1989

al, a. केन्द्र पुस्तकाकव L. D. C. LIBRARY.

APPROVAL SHEET

This special project entitled "Study and Simulation of Robotic Finger Movements" by K. Puhazhendi is approved in partial fufillment of the requirements for the Master's degree in Industrial Design.

Signature

Date

GUIDE

Arpela

28/4/89.

ACKNOWLEDGEMENT

I express my sincere gratitude to my guide , Prot.A.G.Rao for his invaluable guidance and suggestions which have made this projects possible.

I thank all my friends, colleagues and staff of the IDC for their kind help.

April.7,1989 (K. PUHAZHENDI)
IIT Powai,
BOMBAY.

CONTENTS

INTRODUCTION

STUDY AND CLASSIFICATION OF ROBOTIC GRIPPER

BIOLOGICAL GRIPPING MECHANISM

CLASSIFICATION CHART

SIMULATION


BIBLIOGRAPHY


INTRODUCTION

The Robotic finger is an end effector which is called as Grippers. The gripper is the device mounted at the distal end of a robot arm, enabling it to pick up workpieces and hold, manipulate, transfer, place and release them accurately in a discrete position. Thus the gripper is all important mechanical interface between robot and encironment without which, in many circumstances, the robot can not function effectively irrespective of the degree of sophistication it may otherwise possess.


The project consists of two parts namely, a study of existing gripping mechanisms and study of Biological gripping mechanisms. The aim of the work is to provide the designer with a data base of various gripping mechanisms and their related biological mechanisms so as to provide a framework in which the designer can link the two approaches to solve specific gripping problems. This is done by giving a rough classification based on various parameters like type of


mechanism, scope of utility etc. of available gripping mechanisms and certain biological grippers. A study of their functioning is provided to enable the designer to grasp the fundamentals and also to evolve his own classification methodology fitting to his applications.





Vacuum pad





Pads used for non-flat objects

STUDY AND CLASSIFICATION OF ROBOTIC GRIPPER

The grippers can be classified in many ways but the broad classification can be done by considering its mechanisms and functions and the types of objects in grips.

Based on gripping activity, it is classified in to three categories:

- 1. Unilateral gripper,
- 2. Bilateral gripper,
- 3. Multilateral gripper.

1. UNILATERAL GRIPPER

The gripper of this category has only one surface which comes into contact with the object to be handled.


TYPES

1.1 Vacuum clamping/pad gripper


Vacuum clamping is the application of negative pressure to components so they 'adhere' to the gripper.

1.2 Pressure pad gripper

These are used for handling products unsuited to vacuum pads (eg. card board, wood, etc.). Since the depression in



Magnetic pads: (a) permanent magnet gripping device with release system; (b) magnetic gripping device combined with a piston preventing more than one object being lifted at a time (thin sheet) (a similar system can be devised for vacuum pad grippers)



Adhesive gripper


the pad is much less than that obtained when using a vacuum, the area of contact must be larger. The response time is significant when the surface is large.

1.3 Magnetic pad gripper

The magnetic pad gripper uses permanent magnets or electromagnets and this method is only valid for magnetic materials.


1.4 Adhesive grippers

The grippers make use of sticky tape to pick up and hold the component.




(a) Expandable ring type gripper (b) Expanding mandrel type gripper

In Fig.a the rubber ring, 1 is expandable so that it will grip the exterior surface of the circular shaped container, 2, tightly. Fig.b shows an expanding elastomer mandrel 1, which fits into the bore of a projectile cone, 2, for a straight vertical lift.



Symmetrical - Transitional



Symmetrical - Rotational


10

2. BILATERAL GRIPPER


At least two rigid fingers are necessary to grip an object (as opposed to adhering to it). Depending upon the characteristics of the fingers and the object and also on the state of the surfaces (in which dry friction and local deformability is an important factor during operation), contact between the gripper and the object occurs at two points, along two lines or two areas on the surface.

2.1 Symmetrical gripper

This type of gripper involves symmetrical movement of two fingers (claw, jaw, etc.).





TWO JAW WITH AIR JET
The air jet produces vibrations in the thin top layer fabric material and the tip of the lower jaw of the gripper comes into contact with the vibrating cloth. The robot searches downward so that on continued incremental movement the fabric 'pops' above the lower jaw.





Experimental pin concept device (Note, the shaft was fixed to the left pin holder and was allowed to slide in the right pin holder).

PIN TYPE PARALLEL JAW The two pins(jaws) involves inserting the pins through only the top layer of the fabric, then applying tension to the fabric as the pins are allowed to separate the ply.












Asymmetrical - Translational




Asymmetrical - Rotational








2.2 Asymmetrical gripper

The fingers are having the basic structure as shown in Fig. The shape of the finger depends upon the object: it grasps. These are further classified according to the activating mechanism.









3 MULTILATERAL GRIPPER

The principle common to all these gripping devices is deformation of the gripper according to the shape of the object so as to increase the areas of contact between the gripper and the object.


- 3.1 Simple Multilater gripper
- 3.1.1 Three fingered gripper

 It has three fingers. It holds the object radically inward/outward.


The fingers are moving symmetrically/ asymmetrically. This is similar type of bilateral gripper with three finger.

- 3.2 Anthropomorphic Hand Gripper
 These type of grippers follow the
 anthropomorphic model as much as
 possible.
- 3.2.1 Three fingered gripper


 The end effector with three digits
 (fingers) that is, a thump and two
 fingers.




View of finger system





tilting a case to one side



nut-turning









3.2.2 Two finger and a palm type gripper


It has the ability to pick up on object and draw it into a nested grip against the palm.


3.2.3 Four finger gripper

It has four fingers, assembled
will be approximately anthropomorphic
in geometry.














These type are universal grippers which can hold the object by gripping over the odd shaped profile.


- 1. Mechanical type gripper
 - (i) Solid finger gripper
 - (ii) Flexible finger gripper
- 2. Fluid gripper
- 3.3.1 Mechanical type gripper
- 3.3.1.1 Solid Finger gripper
- 1. Multiple joint manipulator

Its principle of motion consists of a mechanism in which levers housed by springs stretch against amorphous runners in uniform tension by hauling a belt.












2. Multifinger gripper


The functioning principle of this gripping system consists in applying redundant number of constraints to the object to be gripped and in the use of constraints that can be adapted to the shape of the object and locked in their final position, enveloping the object as a cage.








Handling of delicate products




Rotary-type four-fingered gripper capable of gripping arbitrary shaped objects with uniform pressure $\,$

3. Four fingered gripper

This type of gripper has four fingers to grip the object. The fingers are actuated by rope and pulley method. This fingers make contact on the surface of the object.



The Omnigripper




Principle of operation

4. Independent finger with multi joint manipulator


This comprises two parallel slightly separated fingers as in many conventional designs. In this case, however, the fingers each consist of an array of 8xl6 closely spaced pins which can ride vertically up and down independently of each other.

A mechanism exists to ensure that all pins can be forced out to the fully extended position. Once all the pins are fully extended, the gripper can be lowered vertically over an object, so pushing some of the pins up out of the way and hence creating 'customised' fingers which fit the upper surfaces of the part.

To grasp objects, the slightly separated ranks of pins can be brought together.




Three states of a rod unit




Rod lifting and grip sensing scheme


5. Surface adapting vacuum cup

To adapt to local variations in surface angle, each unit was equipped with a miniature ball-joined cup assembly as shown in fig.l. To reduce the effect of shifting which occured while adapting to a work piece surface, the distance between the joint and cup contact surface was kept to a minimum. The lower portion of the ball which contacts the work piece surface during grasping was machined to a dull point to guarantee a consistant distance between the rod and the contacted work piece surface regardless of work piece surface angle.



Surface adapting cup assembly








3.3.1.2 Flexible finger gripper

1. Flexible Linkage gripper

These type multiple linkages which are actuated by rope and pulley arrangement. The basic mechanism of this adapted from snake movement. The links follow the contours of the object and firmly hold it.









3.3.2 Fluid gripper

1. Inflatable flexible gripper


These generally take the form of a flexible but resistant envelope into which fluid is injected under pressure. The flexibility of the envelope means that the object can be grasped due to the elastic deformation of the envelope, which moulds itself to shape. The clamping force proportional to the pressure of the fluid inside the envelope and can be easily controlled according to the fragility of the object.





2. Moulding pad gripper

These type of grippers are having flexible bags contains of free flowing (loose) material that consists of particles of different shapes. These bags will take the shape of the object and the loose materials are tightened by pressure. The tightened particle grips the object.




Moulding pads

BIOLOGICAL GRIPPING MECHANISM

- 1. Unilateral gripper
- 1.1 Chameleon

A Chameleon's tongue tip is sticky and partly prehensile, giving the insect victim no chance. This is of the adhesive type.



3


Hood dock

2. Bilateral gripping mechanism

All of the following mechanisms are basically of the Bilateral rotational type with the form of the finger (jaw, claw, beak) dependent upon the object to be gripped.

2.1 Wood Cock

Most manipulations are performed by the bill. The Wood Cock shows how complex such procedures can be when it plunges its bill deep in to mud to take a worm. When it has reached its prey, the bill tip is opened by the quadrate bones (2) rocking forwards in their seating (3) when muscles (1) contract. This pushes forwards on the jugal bones (4), these in turn push the tip of the upper beak open beyond a thin, hinge like area (5).



+

- 4

.


2


7

)


. 2

J






CHAMELEON



Dripping Force



- 3. Multilateral grippers in Nature
- 1. Chameleon


The tail of the Chameleon is not basically used for gripping. But the mechanism can be adapted for grippers. It rolls its tail like a spiral. This mechanism can be utilised for a gripper which should follow the contour for surface gripping.

2. Snake

The snakes generally wrap arround the object with a helical meeting with the object surface. It generates the gripping force radially inward.


Snakes and Chameleon are of contour adapting flexible type.






3. Birds Leg

This is of the multifingered flexible type gripper with a hook at the end.







O Vacuum pad = Flexible tentacle


4. Octopus


This is of the multifinger flexible type.


The tentacles that surround the mouth, armed with suckers on mascular stalks, help to seize the victim and thrust it between the horny jaws.
















Þ

. .






2


5. Star Fish

This is also of the multifinger flexible type.

Water powers the movement of the star fish's tube feet. It is drawn through a series of tubes into a radical canal supplying each arm. The radial canal divides into two lateral canals, each with a valve and ending in a bulb-like ampulla and a foot. During movement the ampulla contracts, the lateral canal value closes and water is forced into the foot which elongates (A), swings forwards and adheres to the substrate. Longitudinal muscles then contract. shortening the foot (B) and forcing fluid back into the ampulla. Each foot is controlled by an intricate system of nerve fibres and works independently, but during forward movement all the feet in leading arm or arms move in the same direction.



To prise open ashellfish, the starfish makes use of the adhesive force of its tube-feet, firmly attached to the two shell valves. By applying a strong steady pressure the starfish opens the twoshells far.




.

.

`

-1

13.




SIMULATION


The simulation of the 'Robotic' finger movements' has been done in 3D model. The wood cock' beak gripping mechanism was adopted. The function and the biological mechanism was explained in the 'Biological gripping mechanism' section, under Bilateral gripping mechanism.

The basic mechanical structure of the beak movement was developed.

The form and the actuating mechanism can be modified to suit the specific need.

This gripper has a good potential in medical application and random picking of objects.





- 1. "Robot Grippers", eduted by D.T.Pham and W.B.Heginbotham, IFS (Publications) Ltd, UK, 1986.
- 2. "Robot Technology"(vol.4) by Francois
 L'Hote, Jean-Marie Kauffmann, Pierre
 Andre', and Jean-Pierre Taillard,
 Prentice-Hall, Inc., 1983.
- 3. "Robot Hands and the Mechanics of Manipulation" by Mathew T.Mason and J.Kenneth Salisbury ,Jr.,MIT press, Cambridge,London,1985.
- 4. "The Natural World" by Gwynne Vevers Mitchellbeazley, 1977.
- 5. "Life on Earth" by G.Pretto, A.Minelll and M.U.Tanara, Newsweek Books, Newyork 1977.
- 6. "Robotica e strutture naturali" by Centro Ricerche Strutture Naturali, Istituto Europeo Di Design, 1983.

CLASSIFICATION CHART

		Туре	of co	ntact	Force object	betwee	n gripper and	shape of object									
	Good gripping qualifies Types of GRIPPER	Point	Line	Surface	Friction	Dead Stop	o lhers Specify	Ewo dimensional	D prismatic	Tregular curve	O cylindrical	D Innegular	1 Cable				
	Vacuum pad		0				Vacuum	0	0	0							
1,	Pressure pad		12		0			0	0	0	0						
UNILATERAL	Magnetic Pad						Magnetic attraction	0	0								
CNIL	Adhesive						Adhesive	0						1			
	Expandable ring type			0	0		2 7 2 2 2			0	0			1			
	Pincer with two finger		\bigcirc		\bigcirc	\bigcirc		0	0	0	0			+			
BILATERAL	Pin	\bigcirc			0			0						1			
BILA	Two finger and a palm	0	0		0					0	0		0				
	Two finger and a palm	0	0	Palm only	0	0			0	0	0	0					

Physic	cal sta	ite	cons	isten	cy	Surface				ght	temp	pevat	ure	oThers	Type of finger						
Solid	V15 COUS	liquid	Fragile	deformable	resistant	rough	Smooth	Viscid	heavy	light	หญิค	normal	low								
Ø	Ÿ	S	图	B	a	<u>a</u>		Ø	යු	18 m	I'c	J'c	Jċ	× 2							
0		÷	0	\bigcirc	0	4.5	\bigcirc		\bigcirc	\bigcirc		\bigcirc	\bigcirc	(1) (1) (1) (1) (1) (1) (1) (1) (1) (1)	vacuum cup/suction cup						
0			0	\bigcirc	\bigcirc	\bigcirc	\bigcirc			\bigcirc		\bigcirc	\bigcirc		pressure pad						
\bigcirc			0		\bigcirc	\bigcirc	\bigcirc		0	\bigcirc		\bigcirc	0	Ferrous object	Magnetic bar						
\bigcirc			0	0	0	\bigcirc	\bigcirc			\bigcirc			0	Fabric material	Adhesive tape						
\bigcirc			0	0	\bigcirc	\bigcirc	\bigcirc					\bigcirc	0		Flexible ring (Inflatable)						
\bigcirc			0	\bigcirc	\bigcirc	\bigcirc	\bigcirc		\bigcirc	\bigcirc	0	\bigcirc	0		Jaw, claw,						
ili.								2		\bigcirc	0	\bigcirc	\bigcirc	Fabric material	pins						
0				0	\bigcirc	0		0	0	0	0	0	0								
0				0	\bigcirc	0	\bigcirc		0	0	0	0	0		Segmented finger						

Finger	charac		FI	nger	mo	ieme	nts			
Number of finger	Degree of freedom	Rigidity	Surface	symmetrical	Asymmetrical	Rotational	Translational	Internal	External	Remarks
		Flexible	Smooth/ even				- 214 2		\bigcirc	There may be multiple vacuum cups to increase gripping force and the capacity to Carry weight
		Flexible	roug						\bigcirc	Multiple pads can be used
		Solid	even						0	Multiple pads can be used
		Flexible	even						0	
		Flexible	rough/ Smooth	=					0	Flexible rings used for external gripping and expanding mandrels used for internal gripping
2	1	Solid	depends up on object			0	0	0	\bigcirc	The two fingers can also be made flexible depending upon the actual application
2	1	Solid		0			0	\bigcirc		
3	1	Solid		0			0	0	0	
3	3	solid	rough		0	0	0		0	Fingers move rotional rotationally

							76 S & A			
							4300	Many world	6.2	
3	8	Solid	rough/ Smooth		\bigcirc				\bigcirc	
4	16	Solid	rough/ Smooth						\bigcirc	
varies with design		solid	rough		\bigcirc	\bigcirc	\bigcirc	\bigcirc	\bigcirc	Rotational movement is achieved by radial lever type finger for internal gripping only.
varies with design		Solid	rough		\bigcirc	0			\bigcirc	
4	1	Solid	rough	8	\bigcirc		=		\bigcirc	
Varies With design	1	Solid	rough	0			0	\bigcirc	\bigcirc	
varies with design	equal to number of finger	Flexi ble	Smooth	185	\bigcirc		0			
varies with design	equal to number of pinger	solid	rough/ smooth	0	0	0			\bigcirc	
		Flexible	rough/ smooth					0	0	
*		Flexible	rough/ Smooth					0	0	
	*	Flexible	rough/ Smooth						C	This can be classified in both unitateral and Mulfilateral gripper
2	1	Solid/ Flexible	rough/ smooth	C)		\Box	
4	SV.	Flexible	rough/ Smooth		C)		C	

design		solid	rough		\cup	\bigcup	\bigcup	\bigcup		gripping only.
varies with design		Solid	rough		0				\bigcirc	
4	1	Solid	rough		0					
Varies with design	1	Solid	rough	0			0	0	\bigcirc	
varies with design	equal to number of finger	Flexi ble	Smooth		0		0		0	
vari <i>e</i> s with design	equal to number of pinger	solid	rough/ smooth	0	0	0			\bigcirc	
		Flexible	rough/ smooth					0	0	
	****	Flexible	rough/ Smooth	,				0	0	
		Flexible	rough/ Smooth							This can be classified in both unitateral and Multilateral gripper
2	1	Solid/ Flexible	rough/ Smooth	C))
4		Flexible	rough/ &mooth	14 22 24	C					
1		Flexible	rough/ Smooth)			snake wrap the object like helical spring where as chameleon wrap the Eall like spiral
8		Flexible	rough/ smooth		\Box)	47			
5		Flexible	rough/ Smooth		C					Its function is similar to octopus but the tentacles are not as flexible as octopus
		1		+=		+		1=	-	

	Timee Tinger with pain		0	palm	0					\bigcirc	\bigcirc	0							0	10
	Four Finger		0		0				0	0	\bigcirc			•					0	
	Multiple joint manipulator				0				0	0	$\overline{\bigcirc}$				C)				
	Multi finger Gripper	0	0		0	0			0	0	$\overline{\bigcirc}$	0	, de		C)		\bigcirc		
RAL	Four finger (contour adapting)		\bigcirc		0				0	\bigcirc	$\overline{\bigcirc}$	0			0					$\overline{\bigcirc}$
MULTILATERA	Omini Gripper	\bigcirc	\bigcirc			,			0	0	$\overline{\bigcirc}$	0			0			($\overline{\bigcirc}$
MULT	Surface adapting vacuum cup			\bigcirc	0			0	0						Ó	19	($\overline{\bigcirc}$
	Flexible Linkage gripper		`	\bigcirc	0				0	0	\bigcirc	0			0			(
											1	Ś			0	0	. (0		
	chameleon tongue			\bigcirc			Adhesive	\bigcirc				\bigcirc			0	0	(\bigcirc
•	crustacens, Beak ar Ihropods		\bigcirc	\bigcirc	\bigcirc			\bigcirc							0		(0	
	Birds leg	\bigcirc		\bigcirc	\bigcirc	\bigcirc			0			\bigcirc			0		(
•	Snake / Chameleon tail			\bigcirc	0										\bigcirc	,)(50	5
	octopus			\bigcirc			suction					0			\bigcirc			5		5
	Star fish			\bigcirc			Suction								\bigcirc)(
								: #												

		Sagmented anthropomorphic
	00000000	Segmented anthropomorphic
	100000000	opposite pushrod Solid finger
0	00000000	Independent solid fingers
0	00000000	Solid finger
0	00000000	Several independent fingers
Ó		independent rigid finger with freely rotating vacuum cup
0	00000000	Segmented linkage finger
00		-
00	00000000	Flexible finger with adhesive coating
		claw, jaw, pincer
0		segmented finger with hook at the tip
		Flexible linkage
	0000000	Flexible tentacle with vacuum pad
	0000000	Flexible tentacle with vacuum pad

